



LANDINGS AT EXTERIOR DOOR  
TO BE 36" X 36" MIN.

---

NOTES:

1. WALL STUDS ARE TO BE SPACED AT 16" O.C. U.N.O.
2. UNIT CUEAD CAPACITIES ARE BASED ON 1.5 8 15.5

4. ALL PANELS SHALL BE BLOCKED WITH A 2-MIN NOMINAL OR WIDER SPACING WITH EDGE WALKING AT ALL SUPPORTS AND JOINTS.
5. WHERE PANELS ARE APPLIED ON BOTH FACES OF A WALL, SPACING IS LESS THAN 16" O.C. ON EITHER SIDE. PANEL JOINTS SHALL BE OFFSET TO FALL ON DIFFERENT PLACING HEIGHTS.
6. FINDING A FOLDING PANEL, EDGES AND TIE PLAYS SHALL BE SPACED NOMINALLY OR WIDER FOR EDGE WALKING 7" O.C. OR LESS. MAXIMUM SPACING SHALL BE 16" O.C. FOR ALL OTHER PLAYS.
7. FOR SHEET ROCK SHEATHING SHALL BE 5/8 COLLIER TIALS IN LEU OF 5/8 PLYWOOD. PLYWOOD SCHEMES ARE PERMITTED TO SUBSTITUTE FOR 5/8 COLLIER TIALS IF THEIR DIMENSIONS ARE WITHIN 1/8"X16"X96" (BIC PABLE 23002 NOTE C)

## FRAMING NOTES

---

# ILAN WALL SOULBOUL

EDGE	FIELD	EDGE	FILE
------	-------	------	------

2X PL WOOD	2" 6	12"	4"	13"
2X PL WOOD	2" 6	12"	4"	13"

DALE WOOD		3"	12
DALE WOOD		3"	12

NO BETTER	1	1	1
NO BETTER	1	1	1

DAT 16" O.C. U.N.O.

LOCKED WITH 2-INCH NOMINAL OR WIDER FRAMING WITH EDGE NAIL

### ENT FRAMING MEMBERS.

DRYWALLS SHALL BE 5d COOLER NAILS IN LIEU OF 8d NAILS. DRYWALL S

---

---

---

---